



Thermal Industrial Insulation Manufactured By:

Howred Corp.

PRODUCT

GOODTEMP is a high temperature thermal insulation made of expanded perlite and soduim silicate reinforced with fibers to increase impact resistance. This thermal insulation is inhibited, asbestos free high temperature insulation. Being inherently inhibited, GOODTEMP protects austenitic stainless steel piping and equipment from failure due to chloride stress corrosion cracking. GOODTEMP also inhibits corrosion of other ferrous metals. The unique characteristic of bonding millions of vitrified air cells give abundant industrial applications to this inhibited high temperature insulation.

Note:

Goodtemp warrants only that the Goodtemp products sold will be free from defects in material and workmanship for one year. Continued use of products suspected of being defective shall be at the risk of the user. Goodtemp's liability shall be limited to the furnishing of replacement products found to be defective in material and workmanship. Goodtemp shall not be liable for anticipated profits or for special, indirect or consequential damages.

GOODTEMP Block Insulation

1" 1 1/2" 2" 2 1/2" 3" 3 1/2" 4"

All block sections are 1 meter long, widths are 6 in. and 12 in.

Goodtemp Insulation Dimensions

All sections are 1 meter long, diameter in inches

Pipe Size	Insulation I.D.'s	1" Thick O.D.	1 1/2" Thick O.D.	2" Thick O.D.	2 1/2" Thick O.D.	3" Thick O.D.	3 1/2" Thick O.D.	4" Thick O.D.
1/2	.910	2.875	4.000	5.000	6.625	7.625	8.625	9.625
3/4	1.110	2.875	4.000	5.000	6.625	7.635	8.625	9.625
1	1.375	3.500	4.500	5.563	6.625	7.625	8.625	9.625
1 1/4	1.705	3.500	5.000	5.563	6.625	7.625	8.625	9.625
1 1/2	1.960	4.000	5.000	6.625	7.625	8.625	9.625	10.750
2	2.435	4.500	5.563	6.625	7.625	8.625	9.625	10.750
2 1/2	2.935	5.000	6.625	7.625	8.625	9.625	10.750	11.750
3	3.560	5.563	6.625	7.625	8.625	9.625	10.750	11.750
3 1/2	4.060	6.625	7.625	8.625	9.625	10.750	11.750	12.750
4	4.560	6.625	7.625	8.625	9.625	10.750	11.750	12.750
4 1/2	5.060	7.625	8.625	9.625	10.750	11.750	12.750	14.000
5	5.623	7.625	8.625	9.625	10.750	11.750	12.750	14.000
6	6.685	8.625	9.625	10.750	11.750	12.750	14.000	15.000
7	7.695		10.750	11.750	12.750	14.000	15.000	16.000
8	8.695		11.750	12.750	14.000	15.000	16.000	17.000
9	9.705		12.750	14.000	15.000	16.000	17.000	18.000
10	10.840		14.000	15.000	16.000	17.000	18.000	19.000
11	11.850		15.000	16.000	17.000	18.000	19.000	20.000
12	12.860		16.000	17.000	18.000	19.000	20.000	21.000
14	14.120		17.000	18.000	19.000	20.000	21.000	22.000
15	15.120		18.000	19.000	20.000	21.000	22.000	23.000
16	16.150		19.000	20.000	21.000	22.000	23.000	24.000
17	17.130			21.000	22.000	23.000	24.000	25.000
18	18.140			22.000	23.000	24.000	25.000	26.000
19	19.140			23.000	24.000	25.000	26.000	27.000
20	20.150			24.000	25.000	26.000	27.000	28.000
21	21.150			25.000	26.000	27.000	28.000	29.000
22	22.160			26.000	27.000	28.000	29.000	30.000
23	23.160			27.000	28.000	29.000	30.000	31.000
24	24.160			28.000	29.000	30.000	31.000	32.000

Manufactured and Marketed by
Howred Corp.



7887 San Felipe, Suite 122
Houston, Texas 77063
713-781-3980